# GBR500R



## **ENGINE**

Type: 4-stroke, DOHC Displacement: 471 cc, parallel twin-cylinder, 4 valves per cylinder Cooling: liquid Maximum power: 47 hp @ 8,600 rpm Torque: 31.7 lb-ft @ 6,500 rpm (43 Nm)

## **FUEL SYSTEM**

Type: PGM-FI programmed fuel injection system Fuel tank capacity: 4.49 gallons (17 liters)

#### **TRANSMISSION**

Type: 6-speed manual Final transmission: chain

## DIMENSIONS

Overall dimensions (L x W x H): 81.9 x 29.9 x 45.1 in (2,080 mm x 760 mm x 1,145 mm) Wheelbase: 55.5 in (1,410 mm) Seat height: 30.9 in (785 mm) Ground clearance: 5.1 in (130 mm) Curb weight: 423 lb (192 kg)

#### **TIRES**

Front tire: 120/70R-17 Rear tire: 160/60-17

#### **BRAKES**

ABS system: 2-channel ABS Front brake: dual wave discs, 11.65 inch (296 mm) diameter, Nissin® hydraulic calipers with 4 pistons Rear brake: wave disc, 9.4 inch (240 mm) diameter, Nissin® hydraulic caliper with 1 piston

## **SUSPENSION**

Front suspension: Showa® SFF-BP 41 mm inverted fork, 4.3 inch (109 mm) travel Rear suspension: Pro-Link® swingarm with preload adjustment, 4.7 inch (119 mm) travel

## **IGNITION & INSTRUMENTATION**

lgnition type: digital transistorized Instrument panel: 5" TFT display Main headlight: LED

# **SPECIAL FEATURES**

- HSTC torque control (switchable)
- Assist and slipper clutch
- Emergency stop signal (automatic brake light)









