

CRF250RX



ENGINE

Type: 4-stroke, Unicam® DOHC
Displacement: 249 cc, single-cylinder, 4 titanium valves
Cooling: liquid

FUEL SYSTEM

Type: PGM-FI electronic fuel injection system
Fuel tank capacity: 2.11 gallons (8 liters)

TRANSMISSION

Type: 5-speed manual
Final transmission: chain

DIMENSIONS

Overall dimensions (L x W x H): 85.7 x 33.0 x 50.4 in
(2,177 mm x 838 mm x 1,280 mm)
Wheelbase: 58.1 in (1,476 mm)
Seat height: 38.0 in (965 mm)
Ground clearance: 13.2 in (335 mm)
Curb weight: 238 lb (108 kg)

TIRES

Front tire: 90/90-21 dunlop AT81
Rear tire: 120/90-18 dunlop AT81

IGNITION & INSTRUMENTATION

Ignition type: DC CDI

BRAKES

Front brake: 10.2 inch (260 mm) hydraulic disc
Rear brake: 9.4 inch (240 mm) hydraulic disc

SUSPENSION

Front suspension: Showa® inverted fork, 49 mm diameter, adjustable, 12.2 inch (310 mm) travel
Rear suspension: Pro-Link® swingarm with Showa® mono-shock, adjustable, 12.3 inch (313 mm) travel

SPECIAL FEATURES

- "HRC Launch Control" mode, managed by ECU for more aggressive starts
- 3 selectable power delivery levels
- Titanium fuel tank
- Black DID DirtStar rims
- Factory hand guards
- Single exhaust
- Completely redesigned plastics and styling