

PIONEER 1000-6

DLX



ENGINE

Type: 4-stroke, SOHC UniCam®
Displacement: 999 cc, 2 cylinders, 4 valves
Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection (PGM-FI)
Fuel capacity: 7.9 gallons (30 liters)

TRANSMISSION

Type: electric shift 4x4
Final drive: direct rear shaft drive

DIMENSIONES

Type: automatic and semi-automatic with dual clutch Transmission (DCT), 6 speeds and reverse
Final drive: direct shaft drive (front and rear)
Drive modes: 2WD, 4WD, Turf mode, and differential lock

TIRES

Front tires: 27 x 9 - 14
Rear tires: 27 x 11 - 14

BRAKES

Front brake: dual 210 mm hydraulic discs
Rear brake: dual 210 mm hydraulic discs

SUSPENSION

Front suspension: independent double wishbone, 10.5 inch travel (267 mm)
Rear suspension: independent double wishbone, 10 inch travel (254 mm)

IGNITION & INSTRUMENTATION

Ignition type: transistorized with electronic advance

SPECIAL FEATURES

- Number of seats: 6
- Bed capacity 1,000 lb (454 kg)
- Towing capacity 2,500 lb (1,134 kg)
- Includes black aluminum wheels