PIONEER 1000-M5



ENGINE

Type: 4-stroke, SOHC Displacement: 999 cc, 2 cylinders, 4 valves UniCam® Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection (PGM-FI) Fuel capacity: 7.9 gallons (30 liters)

TRANSMISSION

Type: automatic and semi-automatic dual-clutch transmission (DCT), 6 speeds with reverse Final drive: direct shaft drive (front and rear) Drive modes: 2WD, 4WD, Turf mode, and differential lock

DIMENSIONS

Overall dimensions (L x W x H): 116.8 x 62.8 x 77.3 in (2,967 mm x 1,595 mm x 1,964 mm)
Wheelbase: 80.2 in (2,037 mm)
Seat height: 34.3 in (871 mm)
Ground clearance: 13.2 in (335 mm) Curb weight: 1,720 lb (780 kg)

Front tires: 27 x 9 - 14 Rear tires: 27 x 11 - 14

Front brake: dual 210 mm hydraulic discs Rear brake: dual 210 mm hydraulic discs

SUSPENSION

Front suspension: independent double wishbone, 10.6 inch travel (269 mm) Rear suspension: independent double wishbone, 10 inch travel (254 mm)

IGNITION & INSTRUMENTATION

Ignition type: transistorized with electronic advance

SPECIAL FEATURES

- Number of seats: 5
- Bed capacity 1,000 lb (454 kg)
 Towing capacity 2,500 lb (1,134 kg)









