

# SAHARA 300 RALLY



## ENGINE

Type: 4-stroke, single-cylinder, OHC  
Displacement: 293.55 cc  
Cooling: air-cooled  
Maximum power: 24.8 hp @ 7,500 rpm  
Torque: 19.5 lb-ft @ 5,750 rpm (26.4 Nm)

## FUEL SYSTEM

Type: programmed fuel injection system (PGM-FI)  
Fuel tank capacity: 3.6 gallons (13.8 liters)

## TRANSMISSION

Type: 6-speed manual  
Final transmission: chain

## DIMENSIONS

Overall dimensions (L x W x H): 86.4 x 32.6 x 50.0 in  
(2,193 mm x 829 mm x 1,270 mm)  
Wheelbase: 56.1 in (1,425 mm)  
Seat height: 33.8 in (859 mm)  
Ground clearance: 10.6 in (269 mm)  
Curb weight: 324 lb (147 kg)

## TIRES

Front tire: 90/90-21  
Rear tire: 120/80-18

## BRAKES

Dual-channel ABS system  
Front brake: 256 mm disc, hydraulic caliper  
Rear brake: 220 mm disc, hydraulic caliper

## SUSPENSION

Front: telescopic fork with 9.6 inch travel (245 mm)  
Rear: Pro-Link® mono-shock, preload adjustable in 7 positions, 8.9 inch travel (225 mm)

## IGNITION & INSTRUMENTATION

Ignition type: CDI with electronic advance  
Instrument panel: digital  
Main light: LED

## SPECIAL FEATURES

- Assist and slipper clutch
- Emergency brake lights
- Digital display with fuel gauge, trip meters, fuel consumption averages and clock



8752-8715



HONDAMOTOS.CR



MOTOSHONDACR

