

TALON 1000X

FOX LIVE VALVE



ENGINE

Type: 4-stroke, UniCam® SOHC
Displacement: 999 cc, 2 cylinders, 4 valves
Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection (PGM-FI)
Fuel capacity: 6.2 gallons + 1.1-gallon reserve (23.6 liters + 4 liters)

TRANSMISSION

Type: 6-speed automatic dual-clutch transmission (DCT) with reverse and HI/LOW subtransmission
Final drive: direct shaft drive (front and rear)
Drive modes: 2WD and i-4WD
Shift modes: Standard, Sport, and Manual

DIMENSIONS

Overall dimensions (L x W x H): 123.7 x 64 x 75.3 in
(3,142 mm x 1,626 mm x 1,913 mm)
Wheelbase: 87.6 in (2,225 mm)
Seat height: 28 in (711 mm)
Ground clearance: 12.7 in (323 mm)
Curb weight: 1,499 lb (680 kg)

TIRES

Front tires: 28 x 9 - 15
Rear tires: 28 x 11 - 15

BRAKES

Front brake: 190 mm hydraulic disc
Rear brake: 160 mm sealed mechanical drum

SUSPENSION

Front: independent double wishbone, 14.6 inch travel (371 mm), with FOX podium 2.5 shocks and live valve electronic adjustment
Rear: 3-link trailing arm, 15.1 inch travel (384 mm), with FOX podium 2.5 shocks and live valve electronic adjustment

IGNITION & INSTRUMENTATION

Ignition type: full transistorized
Instrument panel: digital
Headlight: LED

SPECIAL FEATURES

- Number of seats: 2
- Includes premium alloy wheels
- Only model with automatic transmission and launch control mode
- ROPS (Roll Over Protection Structure)
- Hill-start assist