

TRANSALP



ENGINE

Type: 4-stroke, OHC, Unicam®
Displacement: 755 cc, parallel twin-cylinder, 4 valves per cylinder
Cooling: liquid
Maximum power: 90.5 hp @ 9,500 rpm
Torque: 55.3 lb-ft @ 7,250 rpm (75 Nm)

FUEL SYSTEM

Type: PGM-FI programmed fuel injection
Fuel tank capacity: 4.46 gallons (16.9 liters)

TRANSMISSION

Type: 6-speed manual
Final transmission: chain

DIMENSIONS

Overall dimensions (L x W x H): 91.5 x 33 x 57.3 in
(2,325 mm x 838 mm x 1,455 mm)
Wheelbase: 61.4 in (1,560 mm)
Seat height: 33.5 in (850 mm)
Ground clearance: 8.3 in (210 mm)
Curb weight: 463 lb (210 kg)

BRAKES

ABS system: switchable on rear wheel
Front brake: dual discs, 12.2 inch (310 mm) diameter,
2-piston calipers
Rear brake: single disc, 10.1 inch (256 mm) diameter,
1-piston caliper

TIRES

Front tire: 90/90-21M/C
Rear tire: 150/70-R18M/C

SUSPENSION

Front suspension: Showa® SFF-CA 43 mm inverted fork,
7.9 inch (200 mm) travel
Rear suspension: Pro-Link® aluminum swingarm with Showa® mono
shock, 7.5 inch (190 mm) travel

IGNITION & INSTRUMENTATION

Ignition type: electric
Instrument panel: 5" TFT display
Connectivity: roadSync
Main headlight: LED

SPECIAL FEATURES

- HSTC torque control with anti-wheelie system
- 4 riding modes + 2 customizable modes
- Electronic throttle
- USB-C connector
- Automatic turn signal cancellation
- Emergency brake signal lights