

TRX520FM6



ENGINE

Type: 4-stroke, OHV
Displacement: 518 cc, 1 cylinder
Cooling: liquid-cooled

FUEL SYSTEM

Type: programmed fuel injection (PGM-FI)
Fuel capacity: 3.9 gallons (14.7 liters)

TRANSMISSION

Type: 4x4 foot-shift
Final drive: front and rear shaft drive with TraxLok® and front differential lock

DIMENSIONS

Overall dimensions (L x W x H): 82.8 x 47.4 x 48 in
(2,103 mm x 1,204 mm x 1,219 mm)
Wheelbase: 50 in (1,270 mm)
Seat height: 34.2 in (869 mm)
Ground clearance: 7.5 in (190 mm)
Curb weight: 635 lb (288 kg)

TIRES

Front tires: 25 x 8 - 12
Rear tires: 25 x 8 - 10-11

BRAKES

Front brake: 190 mm hydraulic disc
Rear brake: 160 mm sealed mechanical drum

SUSPENSION

Front suspension: independent double arm,
7.3 inch travel (185 mm)
Rear suspension: independent double arm,
8.5 inch travel (216 mm)

IGNITION & INSTRUMENTATION

Ignition type: fully transistorized with electronic advance

SPECIAL FEATURES

- Power steering
- Independent suspension
- Manual transmission



8752-8715



HONDAMOTOS.CR



MOTOSHONDACR

